

**FLEXIBLE FLAT TINNED COPPER BRAID GROUND STRAPS
 SOLDER DIPPED ENDS WITH PUNCHED HOLES
 GS-16 UNINSULATED, FOR INSULATED CHANGE P/N TO GSI-16**

*MCM. Add length in Inches (hole to hole) after part number.

Insulation available in Black or Green/Yellow.

The amperage ratings shown are for non-insulated braid and provided as a guide only. These ratings will vary with service conditions, ambient temperature and proximity to other components. All dimensions are nominal.

AWG SIZE	CIRCULAR MIL AREA	NO & AWG OF STRAND	APPROX AMPS	NOM WIDTH	ABLE PART NO.
500MCM	504000	5040 X 30	700	2.250	GS16-500
300MCM	307200	3072 X 30	500	2.125	GS16-300
250MCM	249000	2496 X 30	410	2.125	GS16-250
4/0	225600	2256 X 30	390	2.125	GS16-4/0
3/0	153600	1536 X 30	290	2.000	GS16-3/0
2/0	124800	1248 X 30	250	2.000	GS16-2/0
1/0	105600	1056 X 30	235	1.750	GS16-1/0
1	76800	768 X 30	180	1.625	GS16-001
2	64800	648 X 30	155	1.375	GS16-002
3	52800	528 X 30	145	1.375	GS16-003
4	38400	384 X 30	120	1.000	GS16-004
5	33600	336 X 30	100	1.000	GS16-005
6	24000	240 X 30	93	0.750	GS16-006
7	20800	864 X 36	85	0.750	GS16-007
8	16800	168 X 30	75	0.625	GS16-008
9	13200	528 X 36	62	0.625	GS16-009
10	9600	384 X 30	53	0.375	GS16-010
11	7800	312 X 36	46	0.281	GS16-011
12	6000	240 X 36	40	0.250	GS16-012

Please provide hole size for lugs when placing your order.