

ABL Electronic Supplies, Inc. • 11 South Broad Street • Peekskill, NY 10566
Phone/Fax: 914-736-1-10/1899 • Toll Free Phone/Fax: 1-800-431-2103/932/9225

EXTRA FLEXIBLE SILVER-PLATED GROUND STRAPS

Multiple strands of individual silver plated copper strands conforming to the ASTM B298 standard. 40 micro-inches of silver plating on the braid terminated with electro plated silver ring terminals. Excellent for use at temperatures exceeding 200 deg. C or where special resistance to corrosion is required.

Add length in inches (hole to hole) after part number.

The amperage ratings shown are for non-insulated braid and provided as a guide only. These ratings will vary with service conditions, ambient temperature and proximity to other components. All dimensions are nominal.

AWG SIZE	CIRCULAR MIL AREA	NO & AWG OF STRAND	APPROX AMPS	NOM WIDTH	ABLE PART NO.
1	76800	768 X 30	190	1.625	GSS15-001
2	56700	576 X 30	165	1.500	GSS15-002
3	52800	528 X 30	150	0.875	GSS15-003
5	36000	360 X 30	120	0.750	GSS15-005
6	24000	240 X 30	90	0.750	GSS15-006
7	20800	864 X 36	85	0.750	GSS15-007
9	13200	528 X 36	62	0.625	GSS15-009
10	9600	384 X 36	53	0.500	GSS15-010
11	7630	312 X 36	46	0.375	GSS15-011
12	6000	240 X 36	40	0.250	GSS15-012
14	4200	168 X 36	32	0.250	GSS15-014
15	3000	120 X 36	25	0.187	GSS15-015
16	2400	96 X 36	19	0.156	GSS15-016
19	1200	48 X 36	11	0.093	GSS15-019
22	600	24 X 36	7	0.046	GSS15-022

Please provide hole size for lugs when placing your order.